




PROPRIETARY INFORMATION
COMPANY CONFIDENTIAL




X13





X13

Rubber core Sheel






X13



Waterproof Circle 002



SCREW_CAP



External Rubber core Sheel



X12

NOTES:

1. Current Rating:1.5Amp max @25°C
2. Voltage Rating:35VAC max
3. Insulation Resistance:500 megohms min
4. Contact Resistance:30 milliohms max
5. Withstanding Voltage:1000 VAC
6. Durability:750 Cycles
7. Operating Temperature:-40°C~+85°C
8. Storage Temperature:-50°C~+75°C
9. Waterproof rate:IP67
10. Torque range:15~20 lb.in

ORDER INFORMATION

WAPV-1X 00 - A K Y 0 T
① ② ③④⑤⑥⑦

1. TYPE:

- WAPV-15:WATERPROOF RJ45 MALE FOR 5.0~6.0mm CABLE
- WAPV-17:WATERPROOF RJ45 MALE FOR 7.0~8.1mm CABLE
- WAPV-18:WATERPROOF RJ45 MALE FOR 5.0~6.0mm/7.0~8.1mm CABLE(Include 2 waterproof rubbers)

2. POSITIONS:

00:NONE POSITIONS

3. INSULATOR MATERIAL:

A: PA66

4. INSULATOR COLOR:

K: BLACK

5. CONTACT PLATING:

Y: NONE CONTACT

6. SHIELD PLATING:

O: NONE SHIELD

7. PACKING

T: BAG

X17 X16 Color Option

<p>WAPV-1700-AKY0T Color: Red O' ty: 1pcs</p>	<p>WAPV-1500-AKY0T Color: Bl ack O' ty: 1pcs</p>	<p>WAPV-1800-AKY0T Color: Red and Bl ack O' ty: 2pcs(Left-red+ Ri ght-bl ack)</p>
---	--	---

GENERAL TOLERANCE X.± 0.50 .X± 0.38 .XX± 0.25 .XXX± 0.15	ANGLE TOLERANCE X°± 5.0° .X°± 3.0° .XX°± 2.0° .XXX°± 1.0°	DRAWN	DATE	
		Hill	01/10/18'	
MATERIAL		CHECKED	DATE	PART NUMBER WAPV-1X00-AKY0T
FINISH		APPROVED	DATE	DRAWING NO. GT26-210535
SCALE N/A	UNIT mm	Hill	01/10/18'	SIZE A4 REV. X17
SHEET 1 OF 1				

PROPRIETARY INFORMATION
COMPANY CONFIDENTIAL

REV.	ECN. NO.	DESCRIPTION	ENG	DATE
X4		UPDATE DRAWING	Knight	08/21/15'
X5		CORRECT ERROR	Knight	08/22/15'
X6		UPDATE DRAWING	Dan	10/15/15'
X7		UPDATE DRAWING	Dan	10/27/15'
X8		ADD CABLE SIZE OPTION	Dan	11/02/15'
X9		ADD $\phi 5.00$ CABLE SIZE OPTION	Dan	11/05/15'
X10		Merger CABLE SIZE OPTION	Dan	11/11/15'
X11		Design Changed	Tim	03/28/16'
X12		Update Drawing	Tim	06/06/16'
X13		Design Changed	Tim	06/28/16'
X14		Add Note 10	Tim	07/07/16'
X15		Correct	Tim	08/18/16'
X16		Add Color Option of Rubber	Tim	10/09/16'
X17		Change Packing SPEC	Hill	01/10/18'

**SECTION A-A
MALE COMPONENT**

Male Standard Parts

5	Waterproof Rubber Plug		SILICA GEL	Color See Option
4	Screw Cap	1	PA66 UL 94V-0	BLACK
3	Rubber core Sheel	1	PA66 UL 94V-0	BLACK
2	Waterproof Circle 002	1	SILICA GEL	Nature
1	External Rubber core Sheel	1	PA66 UL 94V-0	BLACK,
ITEM	NAME	Q'TY	DESCRIPTION	NOTE

GENERAL TOLERANCE		ANGLE TOLERANCE	
X. ± 0.50	X° ± 5.0°		
.X ± 0.38	.X° ± 3.0°		
.XX ± 0.25	.XX° ± 2.0°		
.XXX ± 0.15	.XXX° ± 1.0°		
MATERIAL		FINISH	
SCALE <i>N/A</i>		UNIT <i>mm</i>	
SHEET 1 OF 1			

DRAWN	DATE
Hill	01/10/18'
CHECKED	DATE
APPROVED	DATE
Hill	01/10/18'

GENESIS TECHNOLOGY, INC.	
TITLE: Waterproof RJ 45 Male	
PART NUMBER: WAPV-1X00-AKY0T	
DRAWING NO.	SIZE <i>A4</i>
GT26-210535	REV. <i>X17</i>